

# \* PRODUCT INFORMATION \*

## **HUSKEY™ COOLUBE GREASE**

### **DESCRIPTION**

**HUSKEY COOLUBE** grease is a premium quality, multi-purpose, non-soap grease. It gives better lubrication in more applications, wet or dry, over a wider temperature range (-40°F to 440°F), and for longer periods of time than ordinary soap-base greases.

**HUSKEY COOLUBE** is a truly multi-purpose grease. Because of its excellent stability and its E.P. characteristics, it will remain on all metal and bearing surfaces longer than most ordinary greases. Formulated not to melt or run out of bearings even at higher temperatures. The distinctive green color makes it easy to identify during and after lubrication.

### **USAGE**

**HUSKEY COOLUBE** is specifically formulated for use on anti-friction bearings, journals and all general greasing; where a single multi-purpose lubricant is desired for economy, simplification of inventory and general greasing of equipment. Some typical applications include fans, blowers, pumps, conveyor bearings, ball bearings, journal bearings, roller bearings, universal joints and all other lubrication points having sliding or rolling friction which require a multi-purpose grease.

### **ADVANTAGES**

- Wide Temperature Range
- Extremely Water Resistant
- Low Coefficient of Friction
- Reduced Wear
- Non-Melting
- Prevents Rust and Corrosion

### **PACKAGE AVAILABILITY**

Convenient disposable gun-loaded 14 oz. Cartridges  
5 gal. Pail, 15 gal. Keg and 55 gal. Drum



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE

# \* PRODUCT INFORMATION \*

## TYPICAL SPECIFICATIONS

<b><u>DESCRIPTION</u></b>	<b>HUSKEY</b> Product:	COOLUBE
	Color:	Green
	Base Oil:	Petroleum
	Thickener:	Synthetic
	Texture:	Buttery

<b><u>TEST</u></b>	<b><u>ASTM METHOD</u></b>	<b><u>RESULT</u></b>
N.L.G.I. Grade	----	2
Worked Penetration, 60 Strokes	D-217	265-295
Base Oil Viscosity, SUS @ 100°F SUS @ 210°F cSt @ 40°C cSt @ 100°C	D-445	303 51 58 7.3
Pour Point, °F	D-97	-40
Flash Point, °F	D-92	440
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	40

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION make no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

7/09



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE