NSF.) All Seals' NSF 61 Compounds^{*}



NSF 61 COMPOUNDS*

EPDM

- E-5019: 50 durometer, peroxide cured
- E-6006: 60 durometer
- E-6026: 60 durometer, high & low temperature service
- E-6502: 65 durometer
- E-7013: 70 durometer
- E-7020: 70 durometer, peroxide cured, high and low temperature service
- E-7039: 70 durometer, purple color
- E-7045: 70 durometer, low compression set
- E-7050: 70 durometer, chloramine resistant
- E-7053: 70 durometer, WRAS, ACS
- E-7056: 70 durometer, high tear strength
- E-7057: 70 durometer, high tensile strength, peroxide cured
- E-8002: 70 durometer, peroxide cured
- E-8005: 80 durometer
- E-8006: 80 durometer, peroxide cured

- E-8012: 80 durometer, peroxided cured, low temperature
- E-9003: 90 durometer, peroxide cured

NBR

- N-5007: 50 durometer
- N-6010: 60 durometer
- N-7027: 70 durometer, low compression set
- N-7039: 70 durometer
- N-7097: 70 durometer, low water swell
- N-7098: 70 durometer
- N-7503: 75 durometer
- N-8004: 80 durometer

SILICONE

- S-4005: 40 durometer
- S-6004: 60 durometer
- S-7004: 70 durometer
- S-7008: 70 durometer, low compression set
- S-7025: 70 durometer, low compression set
- S-8002: 80 durometer

NSF International is a not-for-profit organization whose mission is to facilitate public health and safety standards, and to provide testing services to those standards. Although conformance to these standards is voluntary, in many industries NSF standards have become the de facto benchmark for consumer product acceptability.

In the rubber industry, the most important standard by far, is the "NSF Standard 61: Drinking Water System Components - Health Effects". Rubber compounds submitted to NSF undergo rigorous testing to determine whether any contaminants leach or migrate from the material while in long term contact with drinking water, and if so, if the level of migration is acceptable from a public health viewpoint.

All Seals is pleased to present a multitude of NSF Standard 61 certified compounds per the adjacent table*. In many cases, these compounds also comply with FDA food contact requirements per 21CFR, 177- 2600, a-d. For more information about NSF, or to check for recent additions to our NSF lineup, please go to www.nsf.org or call our sales department at 800.553.5054.



*NSF/ANSI Standard 61 compounds manufactured by RT Dygert

Why Industry Leaders Rely on All Seals

THE HIGHEST STANDARDS

There's no room for compromise when it comes to public health and safety. All Seals meets and exceeds industry standards. Even when standards are voluntary, we hold ourselves to the highest demands.

A TRUSTED LEADER IN WATER TREATMENT SAFETY

For decades All Seals has been an industry forerunner in water, waste water, water processing, plumbing, chemical processing, food & beverage, and other markets where seals and custom rubber products are crucial.

WE'VE GOT WHAT YOU NEED

We source and stock the widest selection of seals from the finest manufacturers around the world. Our vendors are renowned for their engineering and quality programs, and we have excellent, long term relationships with them. Even in periods of short supply, we can deliver. We can customize any seal precisely to your specifications.

EXTENSIVE VALUE ADDED SERVICES

We provide JIT/Kanban programs, pre-production and kitting, special marking and packaging options, and much more.

FRIENDLY CUSTOMER SERVICE AND EXPERT ON-PREMISES SUPPORT

You're in the best circles with our customer service team. If you need expertise in any area, we've got it, including materials, design, prototyping, testing and more.





CALIFORNIA 20762 Linear Lane Lake Forest, CA 92630 800.553.5054 toll free 714.556.4931 phone 714.557.3257 fax TEXAS 4407 Halik Road, Building A Pearland, TX 77581 800.553.5054 TOLL FREE 281.404.4384 PHONE 281.715.5379 FAX CONTACT

sales@allsealsinc.com

www.allsealsinc.com

© 2016, All Seals, Inc. Rev 8.17

WARRANTIES All Seals, Inc. warrants the products to be free of defects in materials and workmanship (as defined by the engineering print or standard industry specification) for a period of ninety (90) days. Should the product(s), in All Seals, optimication, malfunction during the warranty period, All Seals, Inc. will, at its option, repair or replace the defective product(s) at no charge provided that the product(s) have not been subjected to misuse, abuse, or non-All Seals-authorized alternations, modifications, or repairs. All Seals, Inc. provides only the warranties set forth herein. All other warranties, expressed or implied, including but not limited to the warranties of merchantability and fitness for a particular purpose, are excluded in the event the product(s) provided herein malfuction. Buyer's sole remedy shall be repair or replacement as provided above. Under no circumstances shall All Seals, Inc. the buyer or user for any damages, including any lost profits or other indirect, special, incidental or consequential damages of any kind or nature, arising out of use of, or inability to use such product.