

Metric Seals



26
Metric U-Pkg

Max Pressure: 5000 psi

Type 26 metric U-seals are symmetrical lip, non-loaded U-seals that can be used in rod seal and piston seal applications.

Materials Available: Urethane, NBR, Viton, Silicone, EPR, and Teflon



605/606
Metric U-Pkg

Max Pressure: 5000 psi

Type 605 metric U-seals are dedicated rod seals. They incorporate a twin lip design for improved sealing and stability. Type 606 metric U-seals are dedicated piston seals. They can be used for one piece or split pistons.

Materials Available: Urethane, and NBR



MOR
Metric O-Ring

Max Pressure: varies

Type MOR metric O-rings are "standard" European metric O-rings. These O-rings are used in applications similar to the type OR standard O-ring.

Materials Available: Buna, and Viton



G/P/S/V
JIS O-Ring

Max Pressure: varies

Type G, P, S, and V metric O-rings are Japanese Industrial Standard (JIS) O-rings. These O-rings are used in a variety of applications.

Materials Available: Buna, and Viton



BH
Metric H-Wiper

Max Pressure: 100 psi

The BH metric wiper is a double lip wiper that can be used as both a seal and wiper in a low pressure system. Other styles of metric snap-in and press-in wipers are available.

Materials Available: Hythane, and Urethane



T754
M-Piston Seal

Max Pressure: 5000 psi

T754 rectangular metric piston seals are a two piece piston seal design, combining a urethane outer seal with a square ring expander. These seals are commonly used in a low to medium pressure hydraulic applications.

Materials Available: Urethane with Buna expander



DAS
5-Piece Pst Seal

Max Pressure: 6000 psi

The DAS, 5-piece metric piston seal consists of a Buna seal with two split nylon back-up rings and two split nylon wear rings. This seal can be used with one piece piston and two piece piston head applications.

Materials Available: Buna with nylon back-ups and wear rings



MOS
M-Oil Seal

Max Pressure: 10 psi

Type MOS metric oil seals are usually double lip design, providing light dirt exclusion as well as sealing. These seals are typically rubber coated and spring loaded.

Materials Available: Steel case with Buna or Viton lip



88M
Metric V-Pkg

Max Pressure: 6000 psi

88M metric V-packing sets are available in common metric ID, OD and heights. Most sets come (1-5-1) with a fabric female adaptor, 3 fabric rings, 2 buna rings, and a nylon male adaptor. These sets can be used as rod or piston seals.

Materials Available: Buna/Fabric, Buna, and Nylon